

Ref.	HAV130-52 series 3
Issue	2
Date	01/01/10
Page	1 of 2

## Hillstone – VARICON- automatic constant current DC load bank

Type ref **HAV130-52 series3**

- ✓ Automatic range selection
- ✓ Lead Acid or Ni-cad battery testing
- ✓ Automatic constant current control
- ✓ Wide voltage range up to 130V DC
- ✓ Remote hand held controller
- ✓ Auto stop on time and voltage
- ✓ Digital LCD display
- ✓ Safety isolation contactors
- ✓ Fan fail protection
- ✓ High power up to 52KW
- ✓ Cables included
- ✓ Portable
- ✓ Computer interface option



13KW unit illustrated

The Hillstone **HAV 130-52 series3** load bank is designed for automatic constant current DC battery discharge testing for a wide range of lead acid and ni-cad batteries and incorporates the unique Hillstone VARICON remote hand held controller which provides a cost effective solution to fully automatic load banks.

All units incorporate light weight, force cooled high power resistor elements and several safety features including reverse polarity connection, high battery volts, fan fail, auto shut-down, emergency stop push button and battery isolation of each load circuit via continuously rated DC contactors. The unit also includes automatic battery voltage selection, thereby eliminating incorrect operator use.

Load bank operation - The unit should be connected to a 240V ( 110V optional ) single phase auxiliary mains supply and also to the battery . On power up, the load bank will carry out a self diagnostic check to ensure the equipment is functioning correctly and also check the battery is connected correctly and the battery voltage is within the operating limits of the load bank design. The load bank will then automatically select the appropriate internal circuits which are compatible with the connected battery.

The operator then enters the required stop voltage and discharge time period, followed by the discharge current before commences the test by pressing the START push button.

The battery voltage, load current and elapse time is displayed on the remote hand held controller during the test. The load bank will automatically maintain the load current constant as the battery voltage falls.

When the battery voltage falls to the end of discharge voltage ( or pre-set time period ) the

test will stop by automatic disconnection via internal contactors. The display of elapse time and amperhours discharged will be frozen on the LCD screen. The test can be terminated at any time by pressing the STOP push button.

The load bank also incorporates a PAUSE button which allows the test to be stopped and then re-started without re-setting all the test parameters. The elapse time and amperhours readings will also re-start without resetting to zero. This feature enables operators to remove faulty cells during the test if required. The test can be terminated at any time by pressing the manual STOP push button.

The load bank also incorporates a PAUSE button which allows the test to be stopped and then re-started without re-setting all the test parameters. The elapse time and amperhours readings will also be re-start with resetting to zero. This feature enables operators to remove faulty cells during the test if required.

Ref.	HAV130-52 series3
Issue	2
Date	01/01/10
Page	2 of 2

## Specification

Type ref	HAV130-52 series3		
Nominal DC voltage ranges	24V	50V	110V
Max. DC voltages	32.5V	65V	130V
Max. DC currents	400A	400A	400A
Max power rating	13KW	26KW	52KW
Max. No. lead acid cells	15	30	60
Max. No. Ni-cad cells	22	42	96
Constant current performance ( rating dependant on voltage)	264A at 21.5V	265A at 43V	300A at 97.5V
Load current adjustment	less than 1 amp to max current		
Digital Panel Display	4 line 20 character numerical backlit display		
Display information	Battery volts Discharged Ampere hours	Battery current	Elapse time Test status / fault
Auxiliary mains supply	240V single phase 50 hz		
Mains cable set	2 metre mains cable with IEC socket & UK 13A plug		
Hand held controller cable	5 metres ( longer available on request )		
DC cable set	3 metre twin, flexible cable set with industrial plug/socket		
Case size	1000mm long x 600mm wide x 1350mm high		
Weight	85 kgs		
Finish	Light grey RAL7032 textured finish		
Environmental protection rating	IP21		
Movement	Swivel castors and folk lift facilities ( lifting eyes optional )		
Operating temperature range	0 – 40 deg C		
Storage temperature range	0 – 80 deg C		

### Notes

- 1) Units are designed for indoor use only in a clean, dry and well ventilated environment.
- 2) The available constant current and ratings are proportional to the end of test voltage.
- 3) Information in technical literature, quotations or data sheets are intended to be correct at the time of publication. Hillstone Products Ltd bears no responsibility for the accuracy of any information given.
- 4) We reserve the right to make detail changes to specification, components, dimensions or weights at the time of design or manufacture without prior notice.
- 5) All information in this data sheet is the copyright of Hillstone Products Ltd.
- 6) All designs and software is the intellectual property of Hillstone Products Ltd

### Optional extras

1. 110V auxiliary mains supply
2. Computer interface to transfer battery data to a laptop computer.
3. Extra length battery cables
4. Top lifting eyes

Hillstone Products Ltd  
 Unit 2 Portland Industrial Estate  
 Portland Street, Bury  
 Lancashire England BL9 6EY

Tel. +44 (0) 161 763 3100  
 Fax. +44 (0) 161 763 3158  
 e-mail [sales@hillstone.co.uk](mailto:sales@hillstone.co.uk)  
[www.hillstone.co.uk](http://www.hillstone.co.uk)