

## Hillstone AC load bank, Type ref: **HAC415-26**

- Simple operation
- Fan fail protection
- High power up to 26KW
- Portable
- Circuit breaker protection

The Hillstone **HAC415-26** load bank is designed for AC generator and UPS load testing

All units incorporate light weight, force cooled high power resistor elements



Typical unit illustrated

### Specification

Type ref: HAC415-26	
Nominal AC voltage ranges	415V
Frequency	50Hz
Max power rating	26KW
Minimum Load adjustment	1kW
Panel mounted controls	Fully rated circuit breaker and individual load channel selection switches.
Cable plug connection	63A, 4 pin and earth socket
Cooling Fans	415V 50hz operation derived from the test source
Case size	735 mm long + 40mm front handles 570 mm high + 50mm top handles 575 mm wide
Weight	30kgs
Finish	Light grey 00A05 to a high quality textured paint finish
Resistor types	Mirca card wire tape resistors, $\pm 5\%$ tolerance
Environmental protection rating	IP21 Designed for indoor operation
Operating temperature range	0 – 40 deg C
Storage temperature range	0 – 80 deg C
Movement	Carrying handles and castors
Measurement	4mm shrouded socket for L1, L2, L3, N
Optional Extras	Auxiliary AC fan supply

- Notes**
- 1) Information in technical literature, quotations or data sheets are intended to be correct at the time of publication. Hillstone Products Ltd bears no responsibility for the accuracy of any information given.
  - 2) We reserve the right to make detail changes to specification, components, dimensions or weights at the time of design or manufacture without prior notice.
  - 3) All information in this data sheet is the intellectual property and copyright of Hillstone Products